

General Description:

Using micro trench design and advanced Field Stop (FS) technology, offering superior conduction and switching performances.

RoHS Compliant.



V_{CES}	650	V
I_C	10	A
P_{tot} ($T_C=25^{\circ}C$)	65	W
$V_{CE(sat)}$	1.6	V

Features:

- FS Trench Technology, Positive temperature coefficient
- Low saturation voltage:
 $V_{CE(sat)}$, TYP=1.6V @ $I_C=10A$, $V_{GE}=15V$;
- Low switching loss:
- Halogen free
- Qualified according to JEDEC criteria

Applications

- UPS
- Solar converts
- Charger
- Motor control



Package Parameters

Type	Package	Marking	Packing	Qty
CRG10T65R85SDZ-G	TO-220	G10T65R85SDZ	Tube	25

Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise specified):

Symbol	Parameter	Rating	Units
V_{CES}	Collector-Emitter Voltage	650	V
V_{GES}	Gate- Emitter Voltage	± 20	V
	Gate- Emitter Voltage ($t_p \leq 10\mu\text{s}, D < 0.01$)	± 30	
I_C^{a1}	Collector Current @ $T_C = 25^\circ\text{C}$	20	A
	Collector Current @ $T_C = 100^\circ\text{C}$	10	
I_{CM}	Pulsed Collector Current @ $T_C = 25^\circ\text{C}$	40	A
I_F^{a2}	Diode Continuous Forward Current @ $T_C = 25^\circ\text{C}$	20	A
	Diode Continuous Forward Current @ $T_C = 100^\circ\text{C}$	10	
I_{FM}	Diode Maximum Forward Current	40	A
T_{SC}	Short Circuit Withstand Time @ $V_{GE}=15\text{V}, V_{CE}=400\text{V}$	6	μs
P_D	Power Dissipation @ $T_C = 25^\circ\text{C}$	65	W
	Power Dissipation @ $T_C = 100^\circ\text{C}$	33	
T_J^{a3}	Operating Junction temperature range	$-40 \sim 175$	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	$-55 \sim 150$	$^\circ\text{C}$
T_L	Maximum Temperature for Soldering	270	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$	Thermal Resistance, Junction to case for IGBT	--	2.3	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance, Junction to case for Diode	--	2.4	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	--	62.5	$^\circ\text{C}/\text{W}$

Electrical Characteristics of the IGBT ($T_C = 25^\circ\text{C}$ unless otherwise specified):

Symbol	Parameter	Test Conditions	SPEC			Units
			Min.	Typ.	Max.	
OFF Characteristics						
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$V_{GE}=0V, I_{CE}=250\mu A$	650	--	--	V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0V, V_{CE}=650V$	--	--	1.0	mA
$I_{GES(F)}$	Gate to Emitter Forward Leakage	$V_{GE}=+20V$	--	--	+250	nA
$I_{GES(R)}$	Gate to Source Reverse Leakage	$V_{GE}=-20V$	--	--	-250	nA
ON Characteristics						
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=10A, V_{GE}=15V, T_C=25^{\circ}C$	--	1.6	2.0	V
		$I_C=10A, V_{GE}=15V, T_C=150^{\circ}C$	--	2.0	--	V
$V_{GE(th)}$	Gate Threshold Voltage	$I_C=250\mu A, V_{CE}=V_{GE}$	4		7	V

Pulse width $t_p \leq 300\mu s, \delta \leq 2\%$						
Dynamic Characteristics						
C_{ies}	Input Capacitance	$V_{CE}=30V, V_{GE}=0V$ $f=1MHz$	--	625	--	pF
C_{oes}	Output Capacitance		--	36	--	
C_{res}	Reverse Transfer Capacitance		--	4	--	
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	$V_{CE}=400V, I_c=10A,$ $R_g=10\Omega, V_{GE}=15V,$ Inductive Load, $T_J=25^\circ C$	--	11	--	ns
t_r	Rise Time		--	14	--	
$t_{d(off)}$	Turn-Off Delay Time		--	49	--	
t_f	Fall Time		--	59	--	
E_{on}^{a4}	Turn-On Switching Loss	$V_{CE}=400V, I_c=10A,$ $R_g=10\Omega, V_{GE}=15V,$ Inductive Load, $T_J=150^\circ C$	--	0.27	--	mJ
E_{off}	Turn-Off Switching Loss		--	0.15	--	
E_{ts}	Total Switching Loss		--	0.42	--	
$t_{d(on)}$	Turn-on Delay Time		--	12	--	ns
t_r	Rise Time		--	16	--	
$t_{d(off)}$	Turn-Off Delay Time		--	60	--	
t_f	Fall Time	--	95	--		
E_{on}^{a4}	Turn-On Switching Loss	$V_{CE}=520V, I_c=10A,$ $V_{GE}=15V$	--	0.30	--	mJ
E_{off}	Turn-Off Switching Loss		--	0.20	--	
E_{ts}	Total Switching Loss		--	0.50	--	
Qg	Total Gate Charge	$V_{CE}=520V, I_c=10A,$ $V_{GE}=15V$	--	26	--	nC
Qge	Gate to Emitter Charge		--	6.6	--	
Qgc	Gate to Collector Charge		--	14	--	
Electrical Characteristics of the DIODE ($T_C= 25^\circ C$ unless otherwise specified):						
V_F	Diode Forward Voltage	$I_F=10A, T_C=25^\circ C$	--	1.85	2.3	V
		$I_F=10A, T_C=150^\circ C$		1.5	--	
T_{rr}	Reverse Recovery Time	$I_F=10A$ $di/dt=200A/\mu S$	--	30	--	ns
I_{rrm}	Reverse Recovery Current		--	3.2	--	A
Q_{rr}	Reverse Recovery Charge		--	48	--	nC

Notes:

- a1: The collector DC current is limited by the maximum junction temperature, limited by the bond wire current capacity at $25^\circ C$
- a2: FRD DC forward current is limited by the maximum junction temperature, limited by the bond wire current capacity at $25^\circ C$
- a3: Repetitive rating; pulse width limited by maximum junction temperature $T_{vjop} = 175^\circ C$, the maximum duty cycle is less than 20% (lasting for 60s at most)
- a4: Turn-on losses include diode losses

Typical Performance Characteristics:




Figure 1. Output Characteristics




Figure 2. Output Characteristics




Figure 3. Saturation Voltage Characteristics




Figure 4. Saturation Voltage - T_J Characteristics




Figure 5. Capacitance Characteristics
















Figure 6. Switching Loss- R_G Characteristics


Figure 7. Switching Time- R_g Characteristics

Figure 8. Switching Time- R_g Characteristics

Figure 9. Switching Loss- T_j Characteristics

Figure 10. Switching Time- T_j Characteristics

Figure 11. Switching Time- T_j Characteristics

Figure 12. Switching Loss- I_C Characteristics


Figure 13. Switching Time- I_c Characteristics

Figure 14. Switching Time- I_c Characteristics

Figure 15. Diode Forward Characteristics

Figure 16. Collector Current- T_j Characteristics

Figure 17. Power dissipation

Figure 18. Gate Charge Characteristics




Figure 19. Forward Bias Safe Operating Area





Figure 20. IGBT Transient Thermal Impedance

Package Information



Items	Values(mm)	
	MIN	MAX
A	9.60	10.6
B	15.0	16.0
B1	8.90	9.50
C	4.30	4.80
C1	2.30	3.10
D	1.20	1.40
E	0.70	0.90
F	0.30	0.60
G	1.17	1.37
H	2.70	3.80
L	12.6	14.8
N	2.34	2.74
Q	2.40	3.00
Ø P	3.50	3.90

TO-220 Package

The name and content of poisonous and harmful material in products

Part's Name Limit	Hazardous Substance									
	Pb	Hg	Cd	Cr(VI)	PBB	PBDE	DIBP	DEHP	DBP	BBP
	≤0.1%	≤0.1%	≤0.01%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%
Lead Frame	○	○	○	○	○	○	○	○	○	○
Molding	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
Wire Bonding	○	○	○	○	○	○	○	○	○	○
Solder	×	○	○	○	○	○	○	○	○	○
Note	○: Means the hazardous material is under the criterion of 2011/65/EU. ×: Means the hazardous material exceeds the criterion of 2011/65/EU. The plumbum element of solder exist in products presently, but within the allowed range of Eurogroup's RoHS.									

Warnings

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. It is suggested to be used under 80 percent of the maximum ratings of the device.
2. When installing the heat sink, please pay attention to the torsional moment and the smoothness of the heat sink.
3. IGBTs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
4. This publication is made by Huajing Microelectronics and subject to regular change without notice.

WUXI CHINA RESOURCES HUAJING MICROELECTRONICS CO., LTD.

Add: No.14 Liangxi RD. Wuxi, Jiangsu, China Mail: 214061 <https://www.crmicro.com>
Tel: 0510-85807228 Fax: 0510-85800864

Marketing Part: Post: 214061 Tel / Fax: 0510-85807228-3663/5508
0510-85800360 (Fax)

Application and Service: Post: 214061 Tel / Fax: 0510-85807228-3399 / 2227

Modify :

Version	Modify record
2024V01	Initial release
2025V01	Adjust the template