华润微电子(重庆)有限公司

CRSM010N04L2

SkyMOS2 N-MOSFET 40V, 0.9mΩ, 220A

Features

- Uses CRM(CQ) advanced SkyMOS2 technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent Q_gx$R_{DS(on)}$ product(FOM)
- Qualified according to JEDEC criteria


Product Summary

V_{DS}	40V
$R_{DS(on).typ}$	0.9mΩ
I_D	220A


100% DVDS Tested
100% Avalanche Tested

Applications

- Motor control and drive
- UPS (Uninterrupible Power Supplies)



CRSM010N04L2



Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
CRSM010N04L2	010N04L2	PDFN5*6	Tape&Reel	N/A	N/A	4k/5k

Absolute Maximum Ratings

Parameter	**Symbol**	**Value**	**Unit**
Drain-source voltage	V_{DS}	40	V
Continuous drain current T_C = 25°C (Silicon limit) T_C = 100°C (Silicon limit)	I_D	 220 142	A
Pulsed drain current (T_C = 25°C, t_p limited by T_{jmax})	$I_{D\ pulse}$	880	A
Avalanche energy, single pulse (I_D = 67A, Rg=25Ω)[1]	E_{AS}	898	mJ
Gate-Source voltage	V_{GS}	±20	V
Power dissipation (T_C = 25°C)	P_{tot}	78	W
Operating junction and storage temperature	T_j , T_{stg}	-55...+150	°C

※. Notes:
1.EAS is tested at starting Tj = 25℃, L = 0.5mH, IAS =60A, VGS = 10V.

©China Resources Microelectronics (Chongqing) Limited

Thermal Resistance

Parameter	Symbol	Max	Unit
Thermal resistance, junction – case.	R_{thJC}	1.61	°C/W
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	62	

Electrical Characteristic (at Tj = 25 °C, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Static Characteristic						
Drain-source breakdown voltage	BV_{DSS}	40	-	-	V	V_{GS}=0V, I_D=250μA
		40	-	-	V	V_{GS}=0V, I_D=1mA
Gate threshold voltage	$V_{GS(th)}$	1.2	1.7	2.2	V	V_{DS}=V_{GS},I_D=250μA
Zero gate voltage drain current	I_{DSS}	- -	- -	1 100	μA	V_{DS}=40V,V_{GS}=0V T_j=25°C T_j=125°C
Gate-source leakage current	I_{GSS}	0	-	±100	nA	V_{GS}=±20V,V_{DS}=0V
Drain-source on-state resistance	$R_{DS(on)}$	- -	0.9 1.3	1.1 1.6		V_{GS}=10V, I_D=40A V_{GS}=4.5V, I_D=40A
Transconductance	g_{fs}	105	181	418	S	V_{DS}=5V, I_D=40A
Dynamic Characteristic						
Input Capacitance	C_{iss}	3679	5519	8279	pF	V_{GS}=0V, V_{DS}=20V, f=1MHz
Output Capacitance	C_{oss}	1296	1944	2916		
Reverse Transfer Capacitance	C_{rss}	26	51	102		
Gate Total Charge	Q_G	44	87.0	174	nC	V_{GS}=10V, V_{DS}=20V, I_D=40A
Gate-Source charge	Q_{gs}	4	17	68		
Gate-Drain charge	Q_{gd}	4	15	60		
Turn-on delay time	$t_{d(on)}$	-	15	-	ns	V_{GS}=10V, V_{DD}=20V, R_{G_ext}=2.7Ω
Rise time	t_r	-	84	-		
Turn-off delay time	$t_{d(off)}$	-	51	-		
Fall time	t_f	-	111	-		
Gate resistance	R_G	0.1	0.6	3.0	Ω	V_{GS}=0V, V_{DS}=0V, f=1MHz

©China Resources Microelectronics (Chongqing) Limited

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	0.78	1.4	V	V_{GS}=0V,I_{SD}=40A
Body Diode Reverse Recovery Time	t_{rr}	28	56	112	ns	I_F=40A,dI/dt=100A/μs
Body Diode Reverse Recovery Charge	Q_{rr}	27	54	108	nC	

©China Resources Microelectronics (Chongqing) Limited

Typical Performance Characteristics

Fig 1: Output Characteristics




Fig 2: Transfer Characteristics




Fig 3: Rds(on) vs Drain Current and Gate Voltage




Fig 4: Rds(on) vs Gate Voltage




Fig 5: Rds(on) vs. Temperature





Fig 6: Vgs(th) vs. Temperature



©China Resources Microelectronics (Chongqing) Limited

Fig 7: BVdss vs. Temperature




Fig 8: Capacitance Characteristics




Fig 9: Gate Charge Characteristics




Fig 10: Body-diode Forward Characteristics




Fig 11: Power Dissipation





Fig 12: Drain Current Derating



©China Resources Microelectronics (Chongqing) Limited

Fig 13: Safe Operating Area






Fig 14: Max. Transient Thermal Impedance




©China Resources Microelectronics (Chongqing) Limited


Test Circuit & Waveform


Gate Charge Test Circuit & Waveform







Resistive Switching Test Circuit & Waveforms







Unclamped Inductive Switching (UIS) Test Circuit & Waveforms






Diode Recovery Test Circuit & Waveforms





©China Resources Microelectronics (Chongqing) Limited


Package Outline: PDFN5*6



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.80	1.20	0.031	0.047
A1	0.00	0.05	0.000	0.002
b	0.30	0.51	0.012	0.020
c	0.15	0.35	0.006	0.014
D	4.80	5.40	0.189	0.213
e	1.27 BSC		0.050 BSC	
E	5.66	6.06	0.223	0.239
G	0.30	0.71	0.012	0.028
H	5.90	6.35	0.232	0.250
J	3.32	3.92	0.131	0.154
K	3.61	4.25	0.142	0.167
L1	0.05	0.25	0.002	0.010
L2	0.00	0.15	0.000	0.006
R	0.25 REF		0.010 REF	
θ	0°	12°	0°	12°

©China Resources Microelectronics (Chongqing) Limited

Marking



NOTE:
NXBBAAAAY

N	—Wire Bond code
X	—Assembly location code
BB	—Fab code
AAAA	—Lot code
Y	—Bin code

©China Resources Microelectronics (Chongqing) Limited

Revision History

Revision	Date	Major changes
1.0	2020/2/18	Release of Preliminary version.
1.1	2024/3/18	UPDATE Ron, ID, EAS, Gfs, Capacitances, Gate Charge, Rg, Trr, Qrr, Performance Characteristics, etc

Disclaimer

Unless otherwise specified in the datasheet, the product is designed and qualified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Any and all semicondutor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

CRM(CQ) reserves the right to improve product design, function and reliability without notice.

©China Resources Microelectronics (Chongqing) Limited