

Features

- Uses CRM(CQ) advanced SkyMOS2 technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent $Q_g \times R_{DS(on)}$ product(FOM)
- Qualified according to JEDEC criteria
- Typical ESD (HBM): 400 V
- MSL3 rated


Applications

- Synchronous Rectification for AC/DC Quick Charger
- Battery management
- UPS (Uninterruptible Power Supplies)


Product Summary

V_{DS}	60V
$R_{DS(on)}@10V$ typ	8mΩ
$R_{DS(on)}@4.5V$ typ	11.1mΩ
I_D	12A

100% Avalanche Tested



CRSE095N06L2A



Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
CRSE095N06L2A	S095N06A	SOP-8	Tape&Reel	N/A	N/A	4000pcs

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	60	V
Continuous drain current $T_A = 25^\circ\text{C}$ $T_A = 75^\circ\text{C}$	I_D	12 9	A
Pulsed drain current ($T_A = 25^\circ\text{C}$, t_p limited by T_{jmax})	$I_{D \text{ pulse}}$	48	A
Avalanche energy, single pulse ($L=0.3\text{mH}$, $R_g=25\Omega$)	E_{AS}	31	mJ
Gate-Source voltage	V_{GS}	± 20	V
Power dissipation ($T_A = 25^\circ\text{C}$)	P_{tot}	2.8	W
Operating junction and storage temperature	T_j, T_{stg}	-55...+150	$^\circ\text{C}$

Thermal Resistance

Parameter	Symbol	Max	Unit
Thermal resistance, junction – lead.	R_{thJL}	21.8	°C/W
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	45	

Electrical Characteristic (at $T_j = 25\text{ °C}$, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		

Static Characteristic

Drain-source breakdown voltage	BV_{DSS}	60	66	-	V	$V_{GS}=0V, I_D=250\mu A$
Gate threshold voltage	$V_{GS(th)}$	1.4	1.7	2	V	$V_{DS}=V_{GS}, I_D=250\mu A$
Zero gate voltage drain current	I_{DSS}	-	0.03	1	μA	$V_{DS}=60V, V_{GS}=0V$ $T_j=25\text{ °C}$
		-	-	10		$T_j=125\text{ °C}$
Gate-source leakage current	I_{GSS}	-	10	100	nA	$V_{GS}=20V, V_{DS}=0V$
Drain-source on-state resistance	$R_{DS(on)}$	-	8.0	9.6	mΩ	$V_{GS}=10V, I_D=12A$
		-	11.1	13.3		$V_{GS}=4.5V, I_D=10A$
Transconductance	g_{fs}	-	42.9	-	S	$V_{DS}=5V, I_D=12A$

Dynamic Characteristic

Input Capacitance	C_{iss}	531	1062	2124	pF	$V_{GS}=0V, V_{DS}=30V,$ $f=1MHz$
Output Capacitance	C_{oss}	154	308	616		
Reverse Transfer Capacitance	C_{rss}	10	20	40		
Gate Total Charge	$Q_{G(10V)}$	-	18	36	nC	$V_{ds}=30V$ $I_d=12A$ $V_{gs}=10V$ $f=1MHz$
	$Q_{G(4.5V)}$	-	8.9	17.8		
Gate-Source charge	Q_{gs}	-	3.7	7.4		
Gate-Drain charge	Q_{gd}	-	2.9	5.8		
Turn-on delay time	$t_{d(on)}$	-	8.8	17.6	ns	$V_{GS}=10V, V_{DD}=30V,$ $R_{G_ext}=2.7\Omega$
Rise time	t_r	-	42	84		
Turn-off delay time	$t_{d(off)}$	-	21.5	43		
Fall time	t_f	-	5.4	10.8		
Gate resistance	R_G	-	1.64	3	Ω	$V_{GS}=0V, V_{DS}=0V,$ $f=1MHz$

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	0.7	1	V	$V_{GS}=0V, I_{SD}=10A$
Body Diode Reverse Recovery Time	t_{rr}	-	78	156	ns	$I_F=12A, dI/dt=300A/\mu s$
Body Diode Reverse Recovery Charge	Q_{rr}	-	192	384	nC	

Typical Performance Characteristics

Fig 1: Output Characteristics




Fig 2: Transfer Characteristics




Fig 3: $R_{DS(on)}$ vs Drain Current and Gate Voltage




Fig 4: $R_{DS(on)}$ vs Gate Voltage




Fig 5: $R_{DS(on)}$ vs. Temperature




Fig 6: Capacitance Characteristics




Fig 7: Gate Charge Characteristics




Fig 8: Body-diode Forward Characteristics




Fig 9: Power Dissipation




Fig 10: Drain Current Derating




Fig 11: Safe Operating Area







Fig 12: Max. Transient Thermal Impedance





Test Circuit & Waveform



Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Package Outline: SOP-8



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
A2	1.25	1.65	0.049	0.065
b	0.33	0.51	0.013	0.020
c	0.17	0.25	0.007	0.010
D	4.80	5.00	0.189	0.197
e	1.27 BSC.		0.050 BSC.	
E	3.80	4.00	0.150	0.157
E1	5.80	6.20	0.228	0.244
h	0.25	0.50	0.010	0.020
L	0.40	1.27	0.016	0.050
θ	0°	8°	0°	8°

Revision History

Revision	Date	Major changes
1.1	2019/10/21	Release of formal version.
1.2	2024/4/2	Add Marking.

Disclaimer

Unless otherwise specified in the datasheet, the product is designed and qualified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

CRM(CQ) reserves the right to improve product design, function and reliability without notice.